


- Type:** Single Point
- Material:** Stainless Steel
- Protection:** IP 68
- Features:** Suggested Platform Size: 350x350 mm
- Application:** Bench Scales
Multi Head Weighers
Check Weighers




Specifications:

Capacity		6kg / 12kg / 30kg / 60kg
Accuracy Class		C3
Max. Number of Verification Intervals	n_{max}	3000
Minimum Load Cell Verification Level	v_{min}	$E_{max}/15000$
Temperature Effect on Zero	%FS/10°C	$\leq \pm 0.0190$
Temperature Effect in Sensitivity	%FS/10°C	$\leq \pm 0.0110$
Combined Error	%FS	$\leq \pm 0.0200$
Creep	%FS	$\leq \pm 0.0160$
Output Sensitivity	mv/v	2.0 ± 0.2
Input Resistance	Ω	400 ± 20
Output Resistance	Ω	350 ± 3.5
Insulation Resistance	M Ω	≥ 5000
Zero Balance	%FS	≤ 2.0
Temperature, Compensated	°C	-10 ~ +40
Temperature, Operating	°C	-30 ~ +70
Excitation, Recommended	v	5 ~ 12
Safe Overload	%FS	120
Ultimate Overload	%FS	150
Standard Cable length	m	6.0

Dimensions:



Cap.(kg)	A
6kg, 12kg, 30kg	18.5
60kg	23.5



All dimensions: mm.